

# ENVELOPE TIE-IN DETAILS

- WALL OPTIONS:
- POURED CONCRETE
  - CMU
  - STEEL STUD

TERMINATION BAR WITH APPROVED MECHANICAL FASTENERS SPACED 12" (305mm) O.C.

- WALL AIR BARRIER OPTIONS:
- 705
  - 705FR-A
  - 705VP

SEALANT TO COVER STEP-OFF AND FASTENER HEAD

IF	705	BarriBond LM-800XL
	705FR-A	
IF	705VP	DOW 758 SILICONE

CCW CONTACT ADHESIVE OPTIONS

702**	715**
702 WB	CAV-GRIP
702 LV**	

\*\*NOT FOR USE WITH 705VP

HUNTER XGI CLASS A OR CCW R2+SHEATHE

705 TWF- TERMINATE 1/2" (13mm) FROM EXTERIOR

METAL DRIP EDGE

GRADE

METAL COUNTER FLASHING

CCW MIRADRI 860/861

CCW MIRADRAIN

REFER TO DETAIL 2.1


SLAB

BELOW GRADE INSULATION-R VALUE TO CODE

3/4 CANT STRIP OF CCW-201 SEALANT

DETAIL STRIPS OF CCW MiraDRI 860/861. STRIPS MUST EXTEND A MINIMUM OF 6" VERTICALLY & HORIZONTALLY AT BOTH INSIDE AND OUTSIDE CORNERS

DIMENSIONS	mm	
(A)	6"	153 MIN.

	0	WALL BARRIERS:	BELOW GRADE BARRIERS:	5.1
	REFER TO NOTES	705, 705FR-A OR 705VP	MIRADRI 860/861	
REFER TO SPECS FOR ADDITIONAL INFORMATION				